

insulating matting for under wall tiling

folofoil™



Coupled polyethylene matting. Laid while tiling using the normal tile adhesive, it provides a waterproofing layer. Suitable for vertical wall tiled coverings of shower boxes, it ensures non transmission of humidity in contiguous rooms.

The membrane in a soft and highly elastic material compensates as well small possible movements between the substrate and the covering, while also ensuring the non-transmission of bacteria and harmful substances.

INSTALLATION:

Prior to installation the substrate should be flat, sound, dry and free from contaminants. The mat should be cut to size prior to installation. Waterproof tile adhesive should be applied with a 4mm x 4mm toothed trowel. Press firmly with the trowel using the smooth edge to ensure a good fix to the substrate avoiding the creation of air pockets.

At joins overlap the matting by 5 cm or use the pre-cut FOLOFOIL/15 strips. For a neat finish on corners or around pipes use the pre-formed FOLOFOIL/I and FOLOFOIL/E internal/external corners and FOLOFOIL/T pipe collar.



FOLOFOIL matting in PE polyethylene

Bi-coupled polyethylene matting. Supplied in rolls.

Material: polyethylene coupled on two sides

FOLOFOIL / 15 linear junction in PE polyethylene

Pre-cut strip to make linear or corner junctions.

Material: polyethylene coupled on two sides

FOLOFOIL pre-formed junctions in PE polyethylene

Junctions of the same material as Folofoil matting to help installation in the most critical points, like internal and external corners.

Material: polyethylene coupled on two sides

Data	u.m.	FOLOFOIL
Thickness	mm	0,4
Material	-	PE+PP
Height	mt.	1
Length	mt.	25

Data	u.m.	FOLOFOIL / 15
Thickness	mm	0,4
Material	-	PE+PP
Height	mt.	0,15
Length	mt.	25

Description	A x B	Art.
Internal corner		FOLOFOIL/I
External corner		FOLOFOIL/E
Pipe collar	120 x 120 mm	FOLOFOIL/T